

TECHNICAL FLOOR

NATO STOCK NUMBER: 8340-33-214293



DESCRIPTION

Technical floor of great resistance and durability, of simple use to cover floors for multiple applications. It creates a firm and safe surface for tents, corridors, camps, courtyards, exhibitions and exhibitions, walkways, car parks and driveways, shows, the possibilities are almost limitless. Any land where soil protection is required by users can be covered.

It has entrance ramps that eliminate risks of tripping and facilitate access to mobile systems with wheels, in addition that they have a registry to immobilize the panels.

There are no tools required for assembly, which is done quickly and inexperienced, covers large areas in minutes.

It accepts unevenness on both positive and negative slopes of up to 25 per axis, a quality that at the same time makes it possible to be installed in roll format, and of course in sheets and individual tiles. It complies with anti-slip standards and is resistant to UV rays. Self-draining, non-conductive inert material, resistant to most common chemicals. Can be stored and installed indoors and outdoors.

TECHNICAL FEATURES

- **Material:** Polypropylene copolymer, also available in HDPE (according to demand).
- **Dimensions:** 500 x 250 x 26 mm tile
(Not including assembly tongue and groove). 1m ^ 2: 8 Pieces.
Weight ≈ 600 grs.
- **Operating temperatures:** -40oC - 50oC
- **Static load evenly distributed per m2:**> 40 ton.
- **Suitable surfaces for installation:** Asphalt, concrete, soil, gravel, sand, snow, grass.

